(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 1 September 2005 (01.09.2005)

PCT

(10) International Publication Number WO 2005/081323 A2

(51) International Patent Classification⁷: 29/10, 21/336, 29/739, 21/331

H01L 29/78,

(21) International Application Number:

PCT/IB2005/050595

(22) International Filing Date: 17 February 2005 (17.02.2005)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0403934.3

21 February 2004 (21.02.2004) G

(71) Applicant (for all designated States except US): KONIN-KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and


(75) Inventors/Applicants (for US only): HUANG, Eddie [GB/GB]; c/o Philips Intellectual Property, & Standards, Cross Oak Lane, Redhill Surrey RH1 5HA (GB). GROVER, Raymond, J. [GB/GB]; c/o Philips Intellectual

Property, & Standards, Cross Oak Lane, Redhill Surrey RH1 5HA (GB).

- (74) Agents: WILLIAMSON, Paul, L. et al.; c/o Philips Intellectual Property, & Standards, Cross Oak Lane, Redhill Surrey RH1 5HA (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: TRENCH-GATE SEMICONDUCTOR DEVICES AND THE MANUFACTURE THEREOF



(57) Abstract: A vertical trench-gate semiconductor device wherein the trench-gates extend in stripes, the source regions extend transversely between the trenchgates in stripes, projection (20) of the source stripes across the trench-gates defines intermediate trench portions (22) between the projected source stripes, and mutually spaced regions (14,14°) of the second conductivity type are to provided immediately below the intermediate trench portions (22) which are connected to source potential. The spaced regions serve to selectively shield portions of the trench-gate from the drain region to suppress their contribution to Cgd and hence Qgd. In particular, they shield those portions of the trenchgate which do not contribute to the channel width of the device, without restricting the current path where a channel is formed.



WO 2005/081323 A2



Published:

 without international search report and to be republished upon receipt of that report For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.